ZKTeco Access Control Terminal SpeedFace M4 - Supplier configuration: SpeedFace M4(ZAM210)



Catalogue SKU	RL-ZK-0080
Supplier model	SpeedFace M4(ZAM210)

Royal Link supplier product summary, not a manufacturer-issued datasheet or manual. Specifications reproduce the supplier entry for this SKU. Optional functions, accessories and compatibility depend on configuration; confirm configuration, pricing and availability before ordering.

Product details, source references and enquiries

Supplier specifications

Item	Catalogue specification
Display	5" Touch Screen
Face Capacity	10,000 (1:N)
Palm Capacity	3,000(Optional ZKPalmVein V20.1))
User Capacity	10,000
Transaction Capacity	200,000(Optional:500,000)
Memory	1GB RAM / 8GB Flash
Communication	TCP/IP, Wiegand Input / Output, Wi-Fi(Optional and coming soon), RS485

Item	Catalogue specification
Power Supply	DC 12V 3A
Operating Temperature	-10°C to 50°C
Operating Humidity	10% to 90%
Standard Functions	ID Card, ADMS, Photo Capture, Event Photo Capture, Up to 14-digit User ID, Access Levels, Groups, Holidays, Anti-Passback, Record Query, Schedule Bell, Tamper Switch Alarm, Automatic Status Switch (Effective only under T&A rules), Multiple Verification Methods, T9 Keyboard (Input), AC Push and TA Push Protocol Switch, HTTPs / SSH Backend Access, Mask Detection, Dynamic QR Code (by camera)
Optional Function	ID/IC/Desfire EV1/EV2 , IC, HID, Felica, Power adaptor
Webserver, Video Door Phone	SIP Client (Version2.0), ONVIF (Compatible with Profile S, Profile T, Profile G, Profile C, Profile Q & Profile A), Wi-Fi, POE, SRB, External Bell
Access Control Interface	3rd-party Electric Lock, Door Sensor, Exit Button, Alarm Output, Aux. Input
SDK	AC PUSH SDK by default
Protection Level	IP66
Software	ZKBio CVAccess ((PUSH Protocol) / ZKBio Zlink (BEST Protocol)